

1. DESCRIPTION

Impa Timbacare WB Ext Sealer is a premium quality water based wood varnish for exterior use on wood.

Since it has been developed for exterior wood surfaces, special attention is devoted to the product to ensure that natural wood appearance is retained. It will not flake and therefore future maintenance is easily maintained.

2. FEATURES

- Ideal for use on most wooden surfaces such as garage doors, shutters window frames, doors, garden furniture, gates etc.
- Easy to apply, quick drying and non-hazardous
- Environmentally friendly.
- Low odour
- Has built in UV stabilizers and dry film biocides which make it ideal for outdoor applications, providing long lasting service and weather protection.
- Excellent resistance to stains and repels water and moisture from penetrating the coating.
- Excellent adhesion to new and previously painted wood.
- Excellent **flow** and **leveling** properties
- **Apeo, formadeyde** and **ammonia** free.
- **Impa Mouldtech™** antibacterial, fungal and algae protection
- **Low VOC**

3. LIMITATION

- When coating exterior wood special attention must be given to the adequate sealing and coating of the end grain.
- **NB:** Freshly painted windows, doors and gates must be allowed to dry for at least 12 hours at 23°C before closing.
- **Exterior wood subject to severe climatic conditions and un-seasonal weather should be re-sealed every 1-2 years to prevent substrate degradation.**

4. SURFACE PREPARATION

NOTE: All wood surfaces must be clean, firm and dry. Remove any grease, mortar dropping etc.

- **NEW WOOD:** Sand in the direction of grain, to a smooth finish within 150 grit paper. Remove dust with a damp cloth.
- **PREVIOUSLY VARNISHED WOOD IN GOOD CONDITION:** Sand to a matt finish to create a key. Remove dust with a damp cloth.
- **PREVIOUSLY VARNISHED WOOD IN POOR CONDITION:** Rinse thoroughly with fresh water. Sand to a smooth finish. Remove dust with a damp cloth.
- **WOOD PREVIOUSLY COATED WITH WAX SEALER/OIL BASED WOOD PRESERVATIVE:** Mechanically sand until there is no evidence of residue. Wipe with a mutton cloth and solvent **Restore Cleaning Lacquer Thinners** to remove weathered material and restore surface to an even appearance. Multiple wipes might be necessary

WATERBASE WOOD TREATMENTS

IMPA TIMBACARE WB EXT SEALER

ISSUED DATE : JUNE 2014

TECHNICAL DATA

Product Code
Colour

VA1021
Clear, Teak & Mahogany

Appearance
Shelf life
Packaging
Flashpoint

Gloss
12 Months
1L & 5L
n/a

Viscosity
S.G (weight)
Solids per volume
Solids per mass
VOC

75 – 80KU/23°C
1.02 – 1.04kg/l
34 - 36%
34 - 36%

Practical Spreading rate (depending on porosity)
Recommended finishing coats.

10 - 12m²/L per coat @ 45µm, DFT
2-3 coats

DRYING TIME

Touch dry time
Recoating Time
Full Cure

30 min at 23°C
4 Hour at 23°C
4-7 days

APPLICATION

Roller & Brush

Ready for use

Cleaning
Mixing

Soapy clean water
Stir until homogeneous

- **PREVIOUSLY PAINTED WOOD:** Strip old paint by deep sanding. Rinse thoroughly with fresh water. Sand bare wood to a smooth finish. Remove dust with damp cloth.
- **DISCOLOUR OR WEATHERED WOOD:** Remove discoloured or weathered layer by sanding with 100 grit with **Restore Cleaning Thinners**. Rinse thoroughly with fresh water. Sand to a smooth finish. Remove dust with damp cloth.
- **Knots in wood:** Apply Impa Timbacre Knot Sealer
- **Filler:** If required use **Restore Woodputty**. Sand smooth

5.APPLICATION GUIDE

- Do not apply in a dusty environment
- **NOTE: Do not thin Waterbased Sealer– ready for use**
- Apply the first coat by brush. Allow to dry for 4 hours. Repeat second and third coats in the same manner.
- Apply at least 3 coats to new and old wood.
- Sand lightly between coats with fine paper to de-nib. Remove dust with damp cloth.

6. PRECAUTIONS

- Application should be avoided in cold and moist weather conditions.
- **Do Not** apply the product at surface temperatures below 6°C (minimum of 2°C above dew point) and temperatures above 40°C
- **Do Not** apply if ambient temperature is less than 10°C or more than 40°C.
- **Do Not** apply if relative humidity temperature is less than 10°C or more than 85. °C
- Extremely cold conditions will make the drying time longer.
- Do not apply in dusty environment
- When coating exterior wood special attention must be given to the adequate sealing and coating of the end grain.
- Always keep paint out of reach of children
- Ensure good ventilation during application and drying.
- If accidental contact with skin should occur, wash immediately with soap and water or a recognized skin cleaner.
- Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
- Harmful if swallowed. Seek medical attention and do not induce vomiting.
- Refer to Material Safety Data Sheet for complete information.

Environmental Health & Safety Information

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: LOW & HIGH AROMATIC SOLVENTS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapours and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN AND ANIMALS - DO NOT TAKE INTERNALLY.

Refer to Material Safety Data Sheet for additional health and safety information.

IN CASE OF FIRE: Use foam, CO2, dry chemical, or water fog.

SPILL – Absorb with inert material and dispose of as specified under **Thinning/Clean-up**.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust.

DISCLAIMER

The technical information contained in this document are given in good faith and are meant to be used as a guideline by the specifier or user. Whilst we are confident about the quality of our products, we cannot accept any liability for the incorrect use or application of our products. Surface preparation forms an integral part of the scope of works and it is expected that the highest standards are maintained during surface preparation and application, to ensure that our products perform as intended. Always ensure to use the same product batch numbers, refrain from doing spot touch-ups and paint surfaces from corner to corner to prevent colour and sheen variance. As technology may change over time we reserve the right to change products to keep up with changes in raw materials or product trends without pre notice. Although we will always prevail to keep clients informed about changes to be made, but cannot bind ourselves to such notes Please ensure the use of the latest Technical Data Sheet.

Please note: that all our latest Product Data Sheets and Material Safety Data Sheets are available for viewing on our website at www.impa.co.za. All information listed is owned or used under licence of Impa Paints and its related companies. © 2010 Lurama 149 (Pty) Ltd. All rights is reserved.