

Impa Tennis Court Slush**FS1260/1261****1. PRODUCT DESCRIPTION & BENEFITS:**

Impa Tennis Court Top Coat Color (FS1261) is a 100% acrylic emulsion coating designed for tennis courts and other sport and recreational pavement surfaces.

Color: Available in, dark green, Tan Brown, Grey, and Blue.

Uses: Tennis courts, basketball courts, and other asphalt or concrete multi-purpose surfaces.

2. SURFACE PREPARATION:

Pavement surface must be cleaned entirely of dust, dirt, debris and all loose materials. Repairs of pavement surfaces detect depressions and cracks must be completed prior to application. All repairs must be flush and smooth to adjoining surfaces.

3. NEW ASPHALT SURFACES:

Must cure 14 to 28 days prior to application. It is recommended that any uncoated asphalt surface receive one or more Coats of **Impa Acrylic Base Coat (FS1260)**(See Technical Bulletin) as required by surface roughness and porosity to provide a smooth, dense underlayment for application of colour texture and finish coats

4. NEW CONCRETE SURFACES:

Must cure 28 days prior to application. Concrete surfaces should have a medium broom finish or similar roughened texture. They must never be steel trowelled. Etch surface with Muriatic or Phosphoric Acid and apply Impa Tennis Court Adhesion Promoter prior to colour coating.

5. MIXING PROCEDURES:

Ready-Mix Colour is ready to use. Do not add water. Stir thoroughly prior to application.

6. APPLICATION:

Apply Ready-Mix Colour with a soft rubber squeegee. Allow each coat to thoroughly dry before applying the next coat. Two coats are recommended.

7. COVERAGE:

Approximately, 1 – 2m²/l per coat.

8. DRYING TIME:

Ready-Mix Colour dries in 30 to 60 minutes under optimum drying conditions. Allow 48 hours before allowing foot traffic or play.

9. PRECAUTIONS

- Application should be avoided in cold and moist weather conditions (do not apply the product at temperatures below 6°C or exceed 60°C)
- Pay attention to the preparation of surfaces.
- Apply in a straight direction.
- Preferable not the direct application to new surfaces.
- Pay attention to the preparation of surfaces.
- Do not apply when raining is imminent or forecast.

Environmental Health & Safety Information

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: PROPYLENE ORETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapours and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN AND ANIMALS - DO NOT TAKE INTERNALLY.

Refer to Material Safety Data Sheet for additional health and safety information.

IN CASE OF FIRE: Use foam, CO₂, dry chemical, or water fog.

SPILL – Absorb with inert material and dispose of as specified under **Thinning/Clean-up**.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust.

DISCLAIMER

The technical information contained in this document are given in good faith and are meant to be used as a guideline by the specifier or user. Whilst we are confident about the quality of our products, we cannot accept any liability for the incorrect use or application of our products. Surface preparation forms an integral part of the scope of works and it is expected that the highest standards are maintained during surface preparation and application, to ensure that our products perform as intended. Always ensure to use the same product batch numbers, refrain from doing spot touch-ups and paint surfaces from corner to corner to prevent colour and sheen variance. As technology may change over time we reserve the right to change products to keep up with changes in raw materials or product trends without pre notice. Although we will always strive to keep clients informed about changes to be made, but cannot bind ourselves to such notes Please ensure the use of the latest Technical Data Sheet.

Please note : that all our latest Product Data Sheets and Material Safety Data Sheets are available for viewing on our website at www.impa.co.za . All information listed is owned or used under licence of Impa Paints and its related companies. © 2010 Lurama 149 (Pty) Ltd. All rights is reserved.