

MATERIAL SAFETY DATASHEET

View (M)SDS Section: <u>1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16</u>

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: POOL EPOXY ENAMEL-BASE

Product Code: EP607

Lurama 149 (PTY) Ltd **Company Name:** P.O. Box 29270 Address:

> Danhof 9301

(051) 432 8913 Telephone: (086) 661 3748 Facsimile: **Contact Person:** Mr. J Strohfeldt MSDS Creation Date: 01 May 2014

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Class: Polyamide dispersion

Classification: F, Xn R Phrases: R11, 43 S Phrases: S2, 26, 36/37/39

Hazardous Components % (w/w) CAS no. E.C. No. 2-BUTOXY ETHANOL 612-056-00-5 112-24-3 3.4

SECTION 3: HAZARDS IDENTIFICATION

SAPMA Health Rating: 2-MODERATE- Temporary or minor injury possible even if treatment

given

Inhalation: Harmful

Skin: Highly irritating. Risk of dermatitis. May cause sensitisation

Eye: **Irritating**

Ingestion: Irritating and nauseating

No carcinogenic, mutagenic or genetic effects established

May have short term environmental effects. Contain, monitor & remove



Inhalation:



SECTION 4: FIRST AID MEASURES

Eye contact: Immediately flush eyes with plenty water for 15 to 20

minutes. Get medical attention, if irritation or

symptoms of overexposure persists

Skin contact: Immediately wash skin with soap and plenty of water.

get medical attention if irritation develops or persists. If inhaled, remove to fresh air. If not breathing, give

Artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison

control center immediately. Never give anything by mouth to an

unconscious person.







MATERIAL SAFETY DATASHEET

SECTION 5: FIRE FIGHTING MEASURES

Flammable with toxic fumes.

Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard.

Use foam, CO2, dry powder. Use fog to cool and control. Do not use water jets.

Cool containers in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Ensure sufficient ventilation.

Contain & collect spillage with inert absorbent material and dispose of according to local regulations.

Keep out of drains and sewers.

SECTION 7: HANDELING and STORAGE

Store separately from any reactive substances - oxidizers in particular

Keep away from ignition sources. No open flames. No smoking. Keep containers cool. Store away from direct sun and heat sources.

SECTION 8: EXPOSURE CONTOLS, PERSONAL PROTECTION – EXPOSURE GUIDELINES

| OEL Type: Mixture | CAS | OEL (mg/m³) | OEL (ppm) | STOEL (mg/m³) | STOEL (mg/m³) |
|-------------------|-----|-------------|-----------|---------------|---------------|
| - | - | - | - | - | - |

SAPMA Health Rating:

Inhalation: Skin: Eve:

contact Ingestion:





2-H-A PPE: Respirator and Eye protection

In case of insufficient ventilation, use suitable respiratory protection AVOID CONTACT. Use impervious gloves, apron and boots Use face shield & goggles or full face respirator/hood. Avoid direct

Observe the rules of hygiene. Wash before eating, drinking or smoking.

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Appearance: White viscous liquid

Flash Point: >23'C 1.030 Density: Viscosity: 68-72 KU

Solubility: Soluble in organic solvents, insoluble in water

SECTION 10: STABILITY and REACTIVITY

Stable under normal conditions

Inert – no reaction with fire- fighting water

Avoid contact with acids, alkalis and hydrocarbon solvents

SECTION 11: TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established

Inspired





MATERIAL SAFETY DATASHEET

SECTION 12: ECOLOGICAL INFORMATION

May have short-term environmental effects; contain, monitor & remove.

SECTION 13: DISPOSAL CONSIDERATIONS

Use reputable waste disposal contractors. Exercise caution in disposal of used containers. Can be eliminated from sewage/ effluent by chemical flocculation.

SECTION 14: TRANSPORTATION INFORMATION

SIN/UN Number: 1263

Shipping Name: Paint

Packaging Group:

Class: 3

SECTION 15: REGULATORY INFORMATION

Classification:

R10 Flammable

R65 Harmful – may cause lung damage if swallowed

S2 Keep out of reach of children. (Retail sales only)

S13 Keep away from food, drink and animal feeding stuffs

S43 Incase of fire, use water fog, foam or powder – Do not use water jets

S62 If swallowed, do not induce vomiting, seek medical advice immediately

SECTION 16: ADDITIONAL INFORMATION

Take precautionary measures against static discharges. In case of any discomfort always seek medical advice. All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.



